

	3-ton Perfect 16 <sup>®</sup>	5-ton Perfect 16 <sup>®</sup>
<b>Capacity Rating</b>	3 ton (1200 cfm)	5 ton (2000 cfm)
<b>MERV Rating</b>	MERV 16 @ 492 fpm	
<b>Rated Airflow</b>	1400 cfm	2000 cfm
<b>Composite Average Efficiency</b>	E1 (0.3-1.0 μm) = 96.7% E2 (1.0-3.0 μm) = 97.7% E3 (3.0-10.0 μm) = 98.5%	E1 (0.3-1.0 μm) = 95.9% E2 (1.0-3.0 μm) = 97.3% E3 (3.0-10.0 μm) = 98.3%
<b>Pressure Drop</b>	0.18 in H <sub>2</sub> O at 1,200 cfm	0.22 in H <sub>2</sub> O at 2000 cfm
<b>Media Area</b>	170 sq.ft.	210 sq. ft.
<b>Filter Life</b>	3 years (50% duty cycle)	
<b>Dimensions (L x W x H)</b>	25.25" × 21.25" × 21.25"	29.25" × 25.25" × 21.25"
<b>Weight</b>	59 lbs. (27 kg)	74 lbs. (33.5 kg)

For more information, visit [www.iqair.com](http://www.iqair.com) or contact an IQAir Commercial Solutions Specialist at 866-500-4090.